































# 20-40A 2PIN 线式



名称	XT60-M	XT60U-M	XT60H-M	XT60L-M
图片 Picture	180°出线 焊接 	180°出线 焊接 	180°出线 焊接 选配后盖 	180°出线 焊接 选配后盖 
轮廓图 Size				
型号 Item No.	XT60-M. G. Y 	XT60U-M. G. Y 	XT60H-M. G. Y 	XT60L-M. G. Y 
		XT60U-M. N. B 	XT60H-M. N. B 	XT60L-M. N. B 

名称	XT60-F	XT60U-F	XT60H-F	XT60L-F
图片 Picture				
轮廓图 Size				
型号 Item No.	XT60-F. G. Y 	XT60U-F. G. Y 	XT60H-F. G. Y 	XT60L-F. G. Y 
		XT60U-F. N. B 	XT60H-F. N. B 	XT60L-F. N. B 

## 规格 Specifications [ 详见产品规格书 ]

名称 Item No	XT60	XT60U	XT60H	XT60L
额定电流 Rated current	35A MAX(12AWG/△<85℃)			
耐电压 Max Voltage	500V DC			
机械寿命 Mechanical Life	100次			
防护等级 Protection Level	IP40			
工作温度 Temperature	-20℃-120℃			
阻燃等级 Flame retardant	UL94-V0			